suggestions

# SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE invites your written comments and years at which

time it may be reaffirmed,

five

at least every

report

SAE reviews each technical

can celled. ō revised


### NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-T-81714/21B AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-T-81714/21B. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

THIRD ANGLE PROJECTION



PREPARED BY SAE SUBCOMMITTEE AE-8C2



# **AEROSPACE STANDARD**

TERMINAL JUNCTION SYSTEM, TERMINAL JUNCTION BLOCKS, ELECTRONIC, IN-LINE JUNCTIONS, INTEGRAL DIODE, SERIES I

AS81714/21 SHEET 1 OF 4

Printed in the U.S.A.

SSUED

THE COMPLETE REQUIREMENTS FOR ACQUIRING THE BLOCKS DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF SPECIFICATION MIL-T-81714.




FIGURE 1. STYLE 1 ELECTRONIC IN-LINE JUNCTION.

TABLE I. STYLE 1 PART NUMBERS.

		Contacts (see Note 3)	
Part Number 1/	Diode P/N	Size	Part Number
M81714/21-1D001	JAN 1N5618	22	M39029/1-100
M81714/21-1D002	JAN 1N5618	20	M39029/1-101
M81714/21-1D003	JAN 1N4148	20	M39029/1-101
M81714/21-1D004	JAN 1N5620	20	M39029/1-101

 $<sup>\</sup>frac{1}{*}$  See part number explanation, Note 5 Class D




FIGURE 2. STYLE 2 ELECTRONIC IN-LINE JUNCTION.

TABLE II. STYLE 2 PART NUMBERS.

Part Number 1/	Diode P/N	Contacts (see Note 3)	
		Size	Part Number
M81714/21-2D001	1N5061	20	M39029/1-101
M81714/21-2D002	1N5 199	20	M39029/1-101


1/ See part number explanation, Note 5

# REQUIREMENTS:

- 1. MATERIALS:
  - a. CURRENT CARRYING MEMBERS OF THE ELECTRONIC IN-LINE JUNCTION SHALL BE IN ACCORDANCE WITH THE COMPONENT SPECIFICATION.
  - b. HOUSING SHALL BE COVERED BY SHRINK TUBING AND/OR SHROUDED WITH GROMMET MATERIAL.

# NOTES:

- 1. DIMENSIONS ARE IN INCHES.
- 2. MIL-T-81714 REQUIREMENTS APPLY TO BASIC IN-LINE JUNCTION ONLY. FOR RATING AND CHARACTERISTICS OF ELECTRONIC COMPONENT(S), CONSULT COMPONENT SPECIFICATION.
- 3. TOOL FOR CONTACT INSERTING/REMOVAL IS M81969/14-02 AND SHALL BE ORDERED SEPARATELY.
- METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
- 5. THE PART NUMBER CONSISTS OF THE LETTER M, SPECIFICATION SHEET NUMBER, STYLE NUMBER (SEE FIGURES), CLASS, AND ELECTRONIC COMPONENT/CIRCUIT DASH NUMBER (SEE TABLES).



# PART NUMBER EXAMPLE:

M81714/21-1D001

DIODE IN-LINE JUNCTION, SIZE 22, STYLE 1, CLASS D, WITH 001 CIRCUIT (ONE JAN 1N5618 DIODE).

6. CLASSES A, B AND C COMPONENTS ARE INACTIVE FOR NEW DESIGN. ONLY CLASS D COMPONENTS SHALL BE USED FOR DIRECT GOVERNMENT ACQUISITION.